


# LONGFLEX® ROBOTIC FD 938 CY



产品应用

特点

FT2

## 电缆结构

	IEC 60228 6
	TPE
	DIN 47100
	PVC
	RAL 7001

## 技术参数

	: -40 ~ -80	: -5 ~ -60
	/ 2000V/min AC	/ 2000V/min AC
20	200M .km	
	300V	
	: 3D D=	
	5D D=	
	1000	

产品编码	产品规格 (mm <sup>2</sup> )	电缆外径 (mm)	铜用量 (kg/km)	电缆净重 (kg/km)
ZL5938071	2× 0.25	5.00	17.14	42.40
ZL5938099	3× 0.25	5.20	20.41	47.44
ZL5938100	4× 0.25	5.50	24.32	54.13
ZL5938101	5× 0.25	5.80	28.3	61.16
ZL5938102	6× 0.25	6.50	32.5	74.98
ZL5938103	7× 0.25	6.90	36.58	82.73
ZL5938104	8× 0.25	7.40	41.75	94.37
ZL5938081	2× 0.34	5.40	20.81	49.60
ZL5938082	3× 0.34	5.60	25.11	56.18
ZL5938072	4× 0.34	6.00	30.19	64.79
ZL5938083	5× 0.34	6.70	35.34	80.34
ZL5938084	6× 0.34	7.10	40.77	90.39
ZL5938085	7× 0.34	7.90	46.04	107.04
ZL5938086	8× 0.34	8.40	52.70	121.28

产品编码	产品规格 (mm <sup>2</sup> )	电缆外径 (mm)	铜用量 (kg/km)	电缆净重 (kg/km)
ZL5938019	2× 0.50	6.00	27.00	60.82
ZL5938105	3× 0.50	6.70	33.20	76.30
ZL5938020	4× 0.50	7.10	40.40	88.38
ZL5938106	5× 0.50	7.90	47.64	107.78
ZL5938107	6× 0.50	8.40	55.29	121.78
ZL5938108	7× 0.50	8.90	62.69	135.62
ZL5938109	8× 0.50	9.50	72.02	154.93
ZL5938025	2× 0.75	7.40	36.00	87.19
ZL5938110	3× 0.75	8.00	44.89	106.65
ZL5938026	4× 0.75	8.50	55.10	124.57
ZL5938111	5× 0.75	9.10	65.35	143.34
ZL5938112	6× 0.75	9.70	76.16	163.50
ZL5938113	7× 0.75	10.70	93.61	198.90